# PROBLEM

#### POSSIBLE CAUSE SOLUTION PREVENTATIVE MAINTENANCE CLOUDY, DULL WATER Dirty filter Clean filter with GLB® Filter Cleanse Backwash as necessary and clean filter filter cleaner. Renew sand filter thoroughly as needed. efficiency with GLB® Filter Rinse Test pH and total alkalinity, Add Test frequently and maintain a pH of pH too high pH Down as directed. Adjust as 7.2-7.8 and a total alkalinity level of 80-120 ppm. Test for chlorine residual and adjust Maintain free chlorine level of 1-4 ppm. Free chlorine residual too low as needed with a GLB® sanitizer, such as GLB® Triple Tab® chlorinating tablets. Treat with Oxy-Brite® non-chlorine shock oxidizer Use GLB® Clear Blue® clarifier (1 fl. oz. Use GLB® Clear Blue® clarifier Filter not removing small to coagulate small particles. per 5,000 gals.) weekly. Check filter operation. particles Use GLB® Filter Rinse once a month. Backwashing Backwash less frequently, only sand filters too as recommended by the filter manufacturer's directions often Use GLB® Segua-Sol® seguestering Use GLB® Sequa-Sol® sequestering **Dissolved metals**

### CLOUDY, GREEN WATER

**Green Algae** 

in the water

Use Algimycin® 3000 algaecide or Algimycin® 2000 algaecide to destroy algae. Use GLB® Drop 'N Vac® flocculent to help remove dead algae.

agent to control metals in the water.

Use **Algimycin® 3000** algaecide (6 fl. oz. per 10,000 gals.) weekly.

agent (4 fl. oz. per 10,000 gals.) weekly.

## BROWN AND/OR DARK GREEN SPOTS

Black Algae

Use GLB® SuperSonic per label directions. Add Algimycin® 3000 algaecide or Algimycin® 2000 algaecide as directed and then brush pool surfaces daily until algae is gone. Use GLB® Drop 'N Vac® flocculent to help remove dead aloae.

Use Algimycin® 3000 algaecide (6 fl. oz. per 10,000 gals.) weekly. Adjust returns to provide better water flow over affected area.

## YELLOW SLIME

**Mustard algae** 

Clean filter with GLB® Filter Cleanse or GLB® Filter Fresh® filter cleaner. Brush affected areas. Use Algimycin® 3000 algaecide or Strike Out® Algaecide for Swimming Pools. Use GLB® Drop 'N Vac® flocculent to help remove dead algae. Use Algimycin® 3000 algaecide (6 fl. oz. per 10,000 gals.) weekly.

#### REDDISH BROWN WATER

Iron or manganese dissolved in water Use GLB® Sequa-Sol® sequestering agent to suspend and inactivate stain-causing minerals. For extreme cases, use GLB® Super Sequa-Sol® sequestering agent.

Use **GLB® Sequa-Sol®** sequestering agent (8 fl. oz. per 10,000 gals.) weekly.

# SOLVER

#### POSSIBLE CAUSE SOLUTION PREVENTATIVE MAINTENANCE CLEAR, GREEN WATER Use GLB® Sequa-Sol® or GLB® Use GLB® Sequa-Sol® sequestering Dissolved copper Super Segua-Sol® seguestering agent (8 fl. oz. per 10,000 gals.) weekly. from fill water; Corrosion of copper agents as directed. Test and adjust pipes or heater the pH and total alkalinity. STAINS & RUST Metals in water Use GLB® Stain Magnet to remove Use GLB® Sequa-Sol® sequestering stains. Follow with GLB® Sequaagent (8 fl. oz. per 10,000 gals.) weekly. Sol® or GLB® Super Sequa-Sol® sequestering agents as directed Make necessary pH and total Maintain pH of 7.2-7.8 and total Unbalanced alkalinity adjustments. alkalinity of 80-120 ppm. water CALCIUM, SCALE DEPOSITS pH or alkalinity Correct with pH Down as directed. Use GLB® Sequa-Sol® or GLB® Super too high Segua-Sol® seguestering agents **Calcium content** Dilute pool water with water of Use GLB® Sequa-Sol® or GLB® Super lower hardness. Use GLB® Sequa-Segua-Sol® seguestering agents too high Sol® or GLB® Super Segua-Sol® weekly. sequestering agents as directed. SKIN & EYE IRRITATION Treat with Oxy-Brite® non-chlorine Combined Maintain available chlorine level of chlorine level is shock oxidizer then test the free 1-4 ppm at all times regardless of pool too high chlorine level and adjust to maintain usage or weather conditions. a residual of 1-4 ppm. Test pH and correct with pH Up or Maintain pH of 7.2-7.8 and total pH too low or alkalinity of 80-120 ppm. too high pH Down

# CHLORINE ODOR Combined

chlorine level is too high Treat with **Oxy-Brite®** non-chlorine shock oxidizer. Test the free chlorine level and adjust to maintain a residual of 1-4 nom.

Test chlorine level daily. Maintain pH of e 7.2-7.8, total alkalinity of 80-120 ppm and a free chlorine level of 1-4 ppm.

## SCUM & ODORS

Grease and oil from swimmers

Use enzyme-action GLB® Natural Clear® Clarifier to dissolve oils and lotions. Clean walls and surfaces with GLB® TLC® surface cleaner. Clean filter with GLB® Filter Tesh® filter Cleanse, GLB® Filter Fresh® filter cleaner or GLB® Filter Rinse.

Shower before entering pool. Maintain a clean filter with periodic cleaning. Treat with Oxy-Brite® non-chlorine shock oxidizer after heavy pool use. Use GLB® Natural Clear® Clarifier weekly.

All trademarks are owned by Innovative Water Care or its affiliates. © 2019 Innovative Water Care All rights reserved. #80129 / #05906651 (4/19)



POOL CARE GUIDE



# Welcome to **GLB**° Pool Care!

This easy-to-use reference guide will walk you through the simple steps of caring for your pool from opening day until you close for the winter.

To get started, you will need to know the size of your pool.

Here's how to calculate the gallons:

Rectangular pool: (length x width x average depth) x 7.5 Round/Oval pool: (length x width x average depth) x 5.9

My pool is gallons.

As you care for your pool, it is important for your pool water to be in "balance." Keeping the water chemistry balanced will prevent the water from becoming corrosive or forming scale deposits, both of which can damage pool equipment.

Your pool water should always range in the following chemistry levels:

Total Alkalinity: 80 - 120 ppm

pH: 7.2 - 7.8

# Sanitizer Level: 1 - 4 ppm

# When caring for your pool, keep these precautions in mind:

- Always read label directions prior to using and use only as directed.
- Always add the chemical to water and not water to the chemical.
- Never add chemicals to the water when people are in the pool.
- Never mix one product with another prior to adding it. to the water.
- Always store pool management products in a cool dry location out of direct sunlight.

# **SEASON STARTUP**

Refresh your pool for the start of the season in only 3 days! **Day One** 

- 1. Ask a professional pool retailer to test the water you will be using to fill your pool. Testing the water will allow you to identify what minerals and water balance factors may require attention later.
- 2. Check that your pool filter is clean. If it is not, use GLB Filter Cleanse according to the directions on the label. Soak the filter overnight for best
- 3. Begin filling the pool, After the pool is filled with several inches of water, add GLB' Sequa-Sol sequestering agent (16 fl. oz. per 10,000 gals.). This sequestering agent will prevent minerals in the water from staining or damaging pool surfaces.
- 4. As the pool completes filling, add GLB Clear Blue Clarifier (4 fl. oz. per 10,000 gals.) to clear the water of small particles. Fill the pool to the middle of the skimmer or the proper level recommended by the manufacturer. Once filled, start the pump and filtration equipment. Run the pool filter overnight or 24 hours if possible. While the filter is running, vacuum and remove any debris from the pool.

### **Day Two**

- 1. Add Oxv-Brite non-chlorine shock oxidizer (1 lb. per 10.000 gals.) to destroy any contaminants that have accumulated in the water.
- 2. Adjust the total alkalinity level into the range of 80 to 120 ppm (parts per million) with GLB Alkalinity Up. Once the total alkalinity is in the ideal range, test the pH levels of the pool water with GLB' Test Strips 4-Way. Add pH Up or pH Down to adjust the pH level into the range of 7.2 to 7.8.
- 3. Next, begin sanitizing the water by adding a GLB sanitizer until you reach the ideal sanitizer level. Allow the water to circulate overnight.

#### **Day Three**

1. Prevent rapid loss of chlorine due to sunlight by adding GLB\* Stabilizer. Note: not applicable for bromine pools.

# **POOL CLOSING**

Ensure an easy spring startup when you close your pool correctly!

# First, prepare the equipment

- 1. Brush pool walls and floor. Vacuum any debris from the pool floor.
- 2. Clean the filter with GLB\* Filter Cleanse.

## Next. treat the water

- 1. Add Oxy-Brite\* non-chlorine shock oxidizer (1 lb. per 10,000 gals.) to destroy organic contaminants.
- 2. Add Algimycin\* Winter algaecide (32 fl. oz. per 10,000 gals. for solid-covered pools, 64 fl. oz. per 10,000 gallons for mesh-covered or uncovered pools) to prevent algae growth throughout the winter.
- 3. Add GLB' Sequa-Sol\* sequestering agent (use the initial dose of 16 fl. oz. per 10,000 gals.) to protect the pool from stains and scale formation. Allow water to circulate for 12-24 hours. If in a mild climate where the pool is left full and uncovered with the filtration system still operating, regularly add your GLB® sanitizer, Algimycin\* 3000 algaecide and GLB Sequa-Sol\* sequestering agent.
- 4. After cleaning and treating the pool, lower the water if you are in an area where the water must be lowered due to freezing conditions. Drain all water from pipes, pumps, heaters, filters and other pool equipment according to the manufacturer's directions. If in a mild climate where the pool is left full and uncovered, refer to the manufacturer's directions regarding filter operation.

# **EASY MAINTENANCE**

Keep your water crystal clear with this easy 3-day routine!

We recommend following these steps on Friday, Sunday and Wednesday, but you can choose any three days that are most convenient for you.

#### FRIDAY

- 1. Test the pH, total alkalinity and sanitizer levels with GLB' Test Strips 4-Way. If necessary, adjust the levels with pH Up, pH Down, GLB Alkalinity Up or by replenishing your sanitizer.
- 2. Add Algimycin\* 3000 algaecide (6 fl. oz. per 10,000 gals.) to prevent
- 3. Add GLB Sequa-Sol sequestering agent (4 fl. oz. per 10,000 gals.) to prevent stains and scale.

#### SUNDAY

- 1. Vacuum the pool and clean out the skimmer basket.
- 2. Wipe off the water line with a soft towel. Occasionally use GLB TLC surface cleaner for heavy buildup at the waterline.
- 3. Add Oxy-Brite' non-chlorine shock oxidizer (1 lb. per 10,000 gals.) to rid water of contaminants.
- 4. Check the filter's operation. Refer to the filter manufacturer's directions regarding when to backwash or clean the filter. Use GLB Filter Cleanse each time the sand filter is backwashed.

### WEDNESDAY

Test the pH, total alkalinity and sanitizer levels with GLB Test Strips 4-Way. If necessary, adjust the levels with pH Up, pH Down, GLB Alkalinity Up or your GLB' sanitizer.

# GLB Pool Closing Kit

For added convenience, use the GLB' Pool Closing Kit, which comes complete with Oxy-Brite non-chlorine shock oxidizer, GLB Sequa-Sol sequestering agent and Algimycin' Winter algaecide.



GLBPool.com