

Recreation Supply Company

P.O. Box 2757 Bismarck, ND 58502-2757

Please fax completed forms to:

800-850-0262

or

701-255-7895

**If you need assistance filling out the forms please call us at
800-437-8072 or 701-222-4860.**

RecordQuest™ Starting Platform ORDER FORM

(To be completed by authorized *Quikblox*™ distributor.)

This form is to be used when ordering *Quikblox*™ starting platforms. Help us serve your clients better by accompanying this form with architectural line drawings and specs for new installations, and line drawings and/or photos for existing applications. Fax to (503) 266-4334.

DISTRIBUTOR INFORMATION:

Date: _____

I. Company: _____
Name: _____
Phone: _____ Email: _____

II. PROJECT OR JOB INFORMATION: (end user)

Institution: _____
Contact Name: _____
Address: _____
City: _____ State: _____ ZIP: _____
Phone: _____ Email: _____

III. STARTING PLATFORM ORDERED (see Spec Sheet for model numbers):

Quikblox™ "World-Class" Model: # _____
 Quikblox™ "RecordQuest" Model: # _____

IV. DEPTH OF WATER AT STARTING LOCATION:

_____ feet _____ inches.

This measurement is to be made at a distance from the pool wall that is specified by applicable ruling bodies. The National Federation of State High School Associations (NFSHSA) prohibits starting blocks in pools with depths of less than 4 feet in the starting end. *Quikblox*™ recommends that starting platforms be installed at the deep end of the pool wherever possible.

V. STARTING PLATFORM HEIGHT:

Height from deck to front of platform: _____ inches
(Measurement "A" on Spec Sheet)

Height from deck to water level: + _____ inches
(Measurement "E" on Spec Sheet)

Height of platform above water level: = _____ inches
(Measurements "A" plus "E" on Spec Sheet)
(Maximum of 30" including thickness of a Relay Judging Platform, if used)

VIII. *Quikblox*™ SPECIAL OPTIONS:

A. *Quikblox*™ Start-Strobes:


- Single strobe – front of platform (additional charge)
- Dual strobe – front and rear of platform (additional charges)

B. Colors (additional charge for custom colors):


- "World Class" model: Standard: White
 Custom Gelcoat: _____
 "RecordQuest" model: Standard: Blue
 Custom Powder-coat: _____

VI. **GUTTER CONFIGURATION:** (Check the diagram which is closest.)


Fully Recessed Gutter




Fully Recessed Gutter w/ Parapet




Partially Recessed Gutter




Rollout Gutter



Flush Gutter & Deck



Flush Gutter with Bull-nose



VII. **ANCHORING INFORMATION:**

A. Parapet dimensions (if applicable):

Width: _____ inches from pool wall to back of parapet (Dimension "G")

Height: _____ inches from deck to top of parapet (Dimension "H")

B. Gutter dimensions:

Width from pool wall to front edge of deck: _____ inches
(Dimension "J" for Partially Recessed or Rollout Gutters)

Height from water level to deck: _____ inches
(Dimension "E" for all decks)

C. Required setback (distance from pool wall to center of stanchion):

Standard 21" – 26" setback (Dimension "F" on Spec Sheet)

Custom setback (Dimension "F" on Spec Sheet)

D. Anchor style desired:

Check box if there are existing anchor stanchions in the deck or bulkhead. If so, fill out the following information.

Single-post anchors ("RecordQuest" model):

1. _____ inches (Inside Dimension – "I.D.")

Dual-post anchors ("World Class" model):

1. _____ inches (Inside Dimension – "I.D.")

2. _____ inches (center-to-center)

Starting Block
Order Forms