



STARTING PLATFORM SUGGESTED MAINTENANCE CHECKLIST

Note: The frequency of inspection and routine maintenance can vary based upon specific equipment use and pool conditions. We recommend that inspections be performed prior to and after each use.

1. **TOP** should:
 - ✓ Be securely affixed to its pedestal and be free of movement
 - ✓ Have a product warning label affixed to the front and rear side of the platform top
 - ✓ Have a non-slip surface
 - ✓ Be parallel to the water surface or at a maximum of 10 degrees pitch towards the pool

2. **ANCHORS** should
 - ✓ Be securely embedded in the concrete deck. There should be no movement or wobble in the anchor
 - ✓ Have all bolt threads functional (not stripped)
 - ✓ Have covers with hardware, and covers are to sit flush with deck so there is no possible trip hazards when the starting platforms are removed

3. **GENERAL**
 - ✓ There is no missing hardware (bolts, screws, washers, lock-washers). Each and every nut and/or bolt should have a lock washer
 - ✓ Every part should be free of cracks, breaks, excessive wear, etc.

Important:

If any of these substandard conditions exist the starting platform, as all pieces of equipment, should be removed from service until properly repaired or replaced.

If you have any questions or require any assistance, please contact your local Paragon Aquatics Distributor or Paragon Aquatics directly.