# **Taylor's FAS-DPD Drop Test Kits**

## **INTRODUCTION**

n recent years, professionals in the pool and spa industry have progressed from using orthotolidine (OT) to N,N-diethyl-p-phenylene-diamine (DPD) when determining chlorine levels with color-matching tests.

The OT method only measures total chlorine—the sum of active and spent sanitizer—which makes maintaining the correct residual a guessing game. Because of this, **regulatory authorities do not permit OT testing in commercial pools.** In addition, orthotolidine contains hydrochloric acid, making it more costly to ship than DPD and therefore more costly to buy.

Unlike OT, the DPD method will distinguish between free available chlorine and total chlorine. By subtracting the free chlorine reading from the total chlorine reading, the amount of combined chlorine in the water can be known. Combined chlorine is not an effective sanitizer. Its presence causes eye and mucous membrane irritation and the characteristic "chlorine" odor of a poorly maintained pool.

Combined chlorine is eliminated by superchlorination. Calculations for the breakpoint dosage depend on knowing the level of combined chlorine in the water, which is why the DPD method is superior to the OT method for testing chlorine-sanitized pools. However, bromine is an effective sanitizer in all its forms. Because of this, either OT or DPD may be used to test bromine pools and spas.

The latest trend in commercial pools with chlorine sanitizer has been the FAS-DPD titration method, which can measure **free and combined chlorine as low as 0.2 ppm** (using a 25 mL sample size) **and as high as 20 ppm** (using a 10 mL sample size).

To get the free chlorine reading, a buffered DPD indicator powder is added to the water sample. It reacts with the chlorine to produce the pink color characteristic of the standard DPD test. Ferrous ammonium sulfate (FAS) titrating reagent is then added until the pink color permanently disappears, signaling the endpoint.

The distinct change from a vibrant pink to no color at all eliminates the need for color matching. This feature comes in handy when testing samples with high levels of sanitizer because the user does not have to distinguish between relatively close printed-color gradations. This test is also a boon for colorblind users.

taylor



Kits with FAS-DPD measure free and combined chlorine precisely without color matching (K-2006 shown). Watch a video demonstration on our website.

The second half of the FAS-DPD test determines the amount of combined chlorine present. It too involves turning the sample from a vibrant pink to a colorless endpoint.

FAS-DPD is available in stand-alone kits to measure chlorine or bromine, and in combination with other common tests.

## **FAS-DPD TEST KITS**

#### K-1515-A\*

Drop test measuring free & combined chlorine; 1 drop = 0.2 or 0.5 ppm; .75 oz. bottles

K-1515-C\*

Same as above but with 2 oz. bottles

### K-1517-A

Drop test measuring total bromine; 1 drop = 0.5 or 1.25 ppm; .75 oz. bottles

#### K-1517-C

Same as above but with 2 oz. bottles

#### K-1518

Drop test measuring free & combined chlorine accurately in the presence of monopersulfate shocks; 1 drop = 0.2 ppm chlorine/1 drop = 0.2 ppm monopersulfate as chlorine; 2 oz. bottles



**Taylor Technologies, Inc.** 410-472-4340 800-TEST KIT (837-8548) www.taylortechnologies.com

ISO 9001:2015 Certified

## FAS-DPD TEST KITS (cont'd)

#### K-2006\* (Spanish: K-2006S\*)

**Complete™:** free & combined chlorine 1 drop = 0.2 or 0.5 ppm; pH (with acid & base demand); total alkalinity; calcium hardness; cyanuric acid; .75 oz. bottles Available in a case pack of six (K-2006-6)

#### K-2006-SALT\*

**Complete™:** Same as K-2006 plus a test for sodium chloride Available in a case pack of six (K-2006-SALT-6)

#### K-2006C\*

Service Complete<sup>™</sup>: Same as K-2006 but with 2 oz. bottles Available in a case pack of eight (K-2006C-8)

#### K-2006C-SALT\*

Service Complete<sup>™</sup>: Same as K-2006C plus a test for sodium chloride

Available in a case pack of eight (K-2006C-SALT-8)

#### K-2106

*Complete*<sup>™</sup>: total bromine 1 drop = 0.5 or 1.25 ppm; pH (with acid & base demand); total alkalinity; calcium hardness; .75 oz. bottles Available in a case pack of six (K-2106-6)

#### K-2009\*

**Pool Inspector™:** free & combined chlorine 1 drop = 0.2 or 0.5 ppm; pH; cyanuric acid (contains 6 bottles of CYA reagent, 4 more than the K-2006); .75 oz. bottles

Available in a case pack of six (K-2009-6)



\* Certified to NSF/ANSI Standard 50. Products labeled with the NSF certification have met the American National Standard for design, construction, and/or performance.

## **USER BENEFITS**

- Titrations do not require the ability to match colors, only the ability to see the permanent color change at the endpoint of the reaction.
- Test kits come complete with all necessary reagents and equipment.
- Waterproof instructions are printed on plasticimpregnated paper that resists fading and tearing.
- Custom-molded, durable plastic cases provide safe storage for all tests and room to store supplemental tests or extra reagents.
- **Proven chemistries** are based on *Standard Methods for the* Examination of Water and Wastewater, APHA, Washington, DC, and/or American Society for Testing and Materials, ASTM, Philadelphia, PA. Some methods use proprietary chemistry developed by Taylor Technologies.

#### **ALSO AVAILABLE**

- Unit Dose Dispenser (#9250) that fits over the vial of DPD powder. When cranked, it serves up the correct amount to run the test, while protecting the powder from exposure to air and humidity.
- Deox Reagent to eliminate interference with the FAS-DPD chlorine test from monopersulfate (non-chlorine) shock treatments in the water; K-2041 (.75 oz.) or K-2042 (2 oz.).
- A wide array of single- and multiparameter kits featuring color-matching and/or drop-count tests.
- Taylor's TTi<sup>®</sup> Colorimeter (M-2000); test more than a dozen parameters commonly encountered in pool/spa settings and transfer results to a PC database.
- Myron L Company portable instruments and calibration solutions (sold separately).
- Testing supplies and kit replacement parts (e.g., burets, flasks, test tubes, and test cells).
- Video demonstrations for new users posted on our website.
- Toll-free technical assistance at 800-TEST KIT.

# **REPRESENTATIVE TEST PROCEDURE**

#### Reproduced from K-2006-SALT instruction:

hese instructions and should be 1. Read precautions on all labels.	4. Replace reagents once each year. 7. Obtair	tubes before and after each test. Instr. #513 1 samples 18" (45 cm) below water surface. ottle vertically when dispensing.
<ul> <li>Rinse and fill large comparator tube to desired mark with water to be tested.</li> <li>Rinse and fill large comparator tube to desired mark with water to be tested.</li> <li>OTE: For 1 drop - 0.2 ppm, use 25 mL sample. For 1 drop - 0.5 ppm, use 10 mL sample.</li> <li>Add 2 dippers R-0870. Swirt until dissolved. If free chlorine is present, sample will turn pink.</li> <li>OTE: Hpink color disappears, add R-0870 until color turns pink.</li> <li>Add R-0871 dropwise, swirling and counting after each drop, until color changes from pink to colories.</li> <li>Multiply drops in Step 3 by drop equivalence (Step 1). Record as parts per million (ppm) free chorine (FC).</li> <li>Add F dops R-0003. Swiri to mix. If combined chlorine is present, sample will turn pink.</li> <li>6. Add R-0871 dropwise, swirling and counting after each drop, until color changes from pink to colordess.</li> <li>7. Multiply drops in Step 6 by drop equivalence (Step 1). Record as ppm combined chlorine (CC).</li> <li><b>PH Test</b></li> <li>1. Rinse and fill large comparator tube to 44 mL mark with water to be tested.</li> <li>2. Add 5 drops R-0004. Cap and invert to mix.</li> <li>3. Match color standard. Record as pH units and save sample if pH needs adjustment. If sample color is between two values, pH is average of the two. To LUWER pH: See acid demand test.</li> <li>7. Add Cho005 dropwise. After each drop, count, mix, and compare with color standards until desired pH is matched. See treatment tables to continue.</li> <li><b>Rese Demand Test</b></li> <li>1. Use treated sample from pH test.</li> <li>2. Add R-0005 dropwise. After each drop, count, mix, and compare with color standards until desired pH is matched. See treatment tables to continue.</li> </ul>	<ul> <li>Total Alkalinity Test</li> <li>1. Rinse and fill large comparator tube to 25 mL mark with water to be tested.</li> <li>2. Add 2 drops R-0007. Swirt to mix.</li> <li>3. Add 5 drops R-0008. Swirt to mix. Sample should turn green.</li> <li>4. Add R-0009 dropwise. After each drop, count and swirt to mix until color changes from green to red.</li> <li>5. Multiply drops in Step 4 by 10. Record as parts per million (ppm) total alkalinity as calcium carbonate.</li> <li>* When high TA is anticipated, this procedure may be used: Use 10 mL sample. J drop R-0007, 3 drops R-0008, and multiply drops in Step 4 by 25.</li> <li>Calcium Hardness Test</li> <li>1. Anse and fill large comparator tube to 25 mL mark with water to be tested.</li> <li>2. Add 20 drops R-0010. Swirt to mix.</li> <li>3. Add 5 drops SR 0011L. Swirt to mix.</li> <li>3. Add 5 drops in Step 4 by 10. Record as parts per million (ppm) calcium hardness a calcium carbonate.</li> <li>* When high CH is anticipated. this procedure may be used: Use 100 to be totated.</li> <li>2. Add 20 drops R-0011. Swirt to mix.</li> <li>3. Add 5 drops for Step 4 by 10. Record as parts per million (ppm) calcium hardness as calcium carbonate.</li> <li>* When high CH is anticipated. this procedure may be used: Use 10 mL samte jub 10 rops F-0010. 3 drops R-0011L, and multiply drops in Step 4 by 25.</li> </ul>	<ul> <li>Cyanuric Acid Test</li> <li>1. Rinse and fill CYA dispensing bottle (#9191) to 7 mL mark with water to be tested.</li> <li>2. Add R-0013 to 14 mL mark. Cap and mix for 30 second</li> <li>3. Slowly transfer cloudy solution to small comparator tub until black dot on bottom just disappears when viewe from top.</li> <li>4. Read tube at liquid level on back of comparator bloc Record reading as parts per million (ppm) cyanuric acid.</li> <li>5. Solum Chloride (Salt) Test</li> <li>For 1 drop - 200 ppm</li> <li>1. Rinse and fill sample tube (#9198) to 10 mL mark with water to be tested.</li> <li>2. Add 1 drop R-0630. Swirl to mix. Sample should turn yellow.</li> <li>3. Add R-0718 dropwise, swirling and counting after each drop, until color changes from yellow to a milky salmon (brick) red. Always hold bottle in vertical position.</li> <li>NDTE: Do not add enough R-0718 to give a brown color. First change from yellow to a milky salmon (brick) red is the endpoint.</li> <li>4. Multiply drops of R-0718 by 200. Record as parts per million (ppm) salt as sodium chloride.</li> </ul>