

## ADA Easy Stair and Easy Ladder Removal

This is a two person operation, and the recommended removal procedure is as follows:

- 1- Slowly lift the rear of the platform up about 6" off the deck and strap on the wheeled dolly across the back.
- 2- One person in the water then slowly lifts the bottom of the Stair up to tilt it on it's back and rest on the gutter rub strips and wheels.

It makes it much easier if the person on the deck also pulls back on the top of the handrails at the same time.

- 3- As the Stair comes up and out the person on the deck keeps pulling back on the handrails to get it further out of the pool.

At this point the white rub strips on the back of the side skirts will be sliding on the edge of the deck lip and support the Stair.

- 4- Both persons continue to slowly pull and push in unison to roll / slide the Stair onto the deck.

The Stair will now be on the deck, laying on it's back and resting on the dolly wheels and rub strips.

To put the Stair back into the pool the recommended procedure is as follows:

- 1- Roll the Stair back into the correct location and position on the deck, with the bottom end slightly overhanging the deck.
- 2- Standing on the deck carefully push the Stair further out into the water area, letting it slowly tilt upright into position.

At this point it will be sliding on the rub strips, and the pool water will also help slow down the Stair as it tilts/slides down into place.

- 3- Remove the dolly and pull the Stair into place against the wall and gutter.
- 4- The final step is to walk down and up the Stair to check the stability, and re-position if required.

It is important to note that all the above operations should be done SLOWLY and CAREFULLY to allow time for the water to flow around, behind, and under the Stair.